

Engineered Low pressure UV Specification

Model No.	RO/DI (m ³ /hr) 99% T ₁₀	Fresh water (m ³ /hr) 94% T ₁₀	Number of lamps	Power Consumption	In/Out Connection
EC400/1	52	41	1	0.44kw	DN 150 - PN 10
EC400/2	123	93	2	0.88kw	DN 150 - PN 10
EC400/3	182	133	3	1.22kw	DN 150 - PN 10
EC400/4	309	214	4	1.78kw	DN 200 - PN 10
EC400/5	376	259	5	2.22kw	DN 200 - PN 10
EC400/6	532	345	6	2.67kw	DN 250 - PN 10
EC400/8	764	481	8	3.5kw	DN 250 - PN 10
EC400/10	1064	634	10	4.44kw	DN 300 - PN 10
EC400/12	1262	753	12	5.3kw	DN 300 - PN 10
EC400/15	1941	1060	15	6.67kw	DN 400 - PN 10
EC400/28	ask	ask	28	ask	ask
EC400/35	ask	ask	35	ask	ask
EC400/50	ask	ask	50	ask	ask

Note :

1. material: S/S AISI 316 polished
2. UV Guaranteed dose : 40mJ/cm2 at the end of lamps life span.
3. Equipment specifications subject to change without notice

European QA Procedures

ISO 9001/2000

CE



榮耀工程股份有限公司
GLORY ENGINEERING & TECHNOLOGY INC.

台北市內湖區 11466 安美街 161 號 4 樓之 1 電話 : +886-2-8792-5521 傳真 : +886-2-8792-5545

統一編號 : 70434850 E-mail : sandman_sun@glorytech.com.tw

<http://www.glorytech.com.tw/>

